

# VERTICAL SYSTEMS INTERNATIONAL

## Model **Vertiveyor** Continuous Vertical Lift

- ★ T Handle Access Door
- ★ Cleanout Access Opening
- ★ Energy Management
- ★ 100% Safety Guarding
- ★ Integrated Control Panel
- ★ Various Sizes Available



- ★ Extensive Safety Guarding
- ★ Can be Designed to Interact with Other Conveyors
- ★ Quiet Operation at Less than 70 Decibels.
- ★ Loading and Unloading in "Z" Pattern Only
- ★ Rates to 40 Loads Per Minute
- ★ Normally Ships in One Piece



The Vertiveyor is a continuous four-strand lift which is modular in design, and capable of handling high daily usage rates. It is capable of supporting high speed operations up to forty loads per minute while consuming a minimal amount of floor space. Because the products conveyed never change orientation, the Vertiveyor is an excellent option for handling products which are apt to slide or tumble on an inclined or spiral conveyor.

### Standard Specifications

- Machine Tapered Sprockets
- T-Handle Access Doors
- Infeed Conveyor With Tunnel Guard
- Energy Management
- Expanded Metal and Lexan Guarding

### Optional Equipment

- Automatic Chain Oiler
- UL Control Panel
- Water Washdown Feature
- Stainless Steel for Food Applications
- Customer Specified Electrical Components
- Tunnel Guards Available
- Special Paint Available
- Doubler for Increased Throughput (Up to 80)
- Plastic Coating on Slats
- Side Drive Motor
- Drip Pan under Drive Motor
- Access Panel for Cleanout

### CAPACITY & PLATFORM DIMENSIONS

MODEL	MAXIMUM WEIGHT (LBS.)	MAXIMUM LENGTH	MAXIMUM WIDTH	MINIMUM ELEVATION
40-50	50	25"	22"	12"
50-100	100	41-1/4"	36"	14"
60-200	200	49-1/2"	48"	16"
80-600	600	62"	52"	20"
100-1200	1200	72-1/2"	64"	24"
120-3000	3000	75"	72"	28"
160-5000	5000	84"	84"	32"

# VERTICAL SYSTEMS INTERNATIONAL

Walton, Kentucky

859-485-9650